

26		28		30		32		34		36		38		40		42		44		46		48			
10	CR904GDXH8	10	CR904GDXH8	10	CR904GDXH8	12	CR1154GDXH8	12	CR1154GDXH8	12	CR1154GDXH8	10	CR904GDXH8	10	CR904GDXH8	12	CR1154GDXH8	12	CR1154GDXH8	12	CR1154GDXH8	12	CR1154GDXH8		
8	CR704GDCH8	10	CR904GDCH8	10	CR904GDCH8	10	CR904GDCH8	12	CR1154GDCH8	12	CR1154GDCH8	10	CR904GDCH8	10	CR904GDCH8	10	CR904GDCH8	12	CR1154GDCH8	12	CR1154GDCH8	12	CR1154GDCH8	12	CR1154GDCH8
8	CR704GDCH8	8	CR704GDCH8	10	CR904GDCH8	10	CR904GDCH8	10	CR904GDCH8	12	CR1154GDCH8	10	CR904GDCH8	10	CR904GDCH8	10	CR904GDCH8	10	CR904GDCH8	12	CR1154GDCH8	12	CR1154GDCH8	12	CR1154GDCH8
												8	CR704GDCH8	10	CR904GDCH8	10	CR904GDCH8	10	CR904GDCH8	10	CR904GDCH8	12	CR1154GDCH8	12	CR1154GDCH8

380-415V - 3 phase, 50Hz

73.0	78.5	85.0	90.0	96.0	101.0	106.5	113.0	118.0	123.5	130.0	135.0
249,100	267,900	290,100	307,100	327,600	344,700	363,400	385,600	402,700	421,400	443,600	460,700
81.5	88.0	95.0	100.5	108.0	113.0	119.5	126.5	132.0	138.0	145.0	150.0
278,100	300,300	324,200	343,000	368,500	385,600	407,800	431,700	450,400	470,900	494,800	511,900
3.15	3.13	3.08	3.04	3.01	2.99	3.10	3.07	3.04	3.02	2.99	2.98
3.50	3.45	3.41	3.34	3.27	3.26	3.42	3.38	3.34	3.31	3.27	3.25
38.0	41.1	45.3	48.6	52.3	55.4	57.0	61.1	63.7	67.1	71.3	74.3
23.2	25.1	27.6	29.6	31.9	33.8	34.4	36.8	38.8	40.9	43.5	45.3
37.8	41.4	45.2	48.8	53.6	56.2	57.3	61.4	64.1	67.6	71.9	75.7
23.3	25.5	27.9	30.1	33.0	34.7	34.9	37.4	39.5	41.7	44.3	46.2

1580 x 2920 x 890
280+(276x2)

1580 x 3935 x 890
280+(276x3)

Silky shade (1Y 8.5/0.5)

Ø 31.75

Ø 38.1

Ø 19.05

Cooling•Dry: -5°C~+43°C D.B., Heating: -20°C~+15°C W.B.

40

60
55
71

61
56
72

62
57
73