

26	28	30	32	34	36	38	40	42	44	46	48
CR904GDZH8	CR1154GDZH8	CR1304GDZH8	CR1404GDZH8	CR904GDZH8	CR904GDZH8	CR904GDZH8	CR904GDZH8	CR904GDZH8	CR1154GDZH8	CR1304GDZH8	CR1404GDZH8
CR1404GDZH8	CR1404GDZH8	CR1404GDZH8	CR1404GDZH8	CR904GDZH8	CR904GDZH8	CR1154GDZH8	CR1304GDZH8	CR1404GDZH8	CR1404GDZH8	CR1404GDZH8	CR1404GDZH8
				CR1304GDZH8	CR1404GDZH8	CR1404GDZH8	CR1404GDZH8	CR1404GDZH8	CR1404GDZH8	CR1404GDZH8	CR1404GDZH8
380-400-415V - 3 phase, 50Hz											
73.0	78.5	85.0	90.0	96.0	101.0	107.0	113.0	118.0	124.0	130.0	135.0
249,100	267,900	290,100	307,100	327,600	344,700	363,400	385,600	402,700	421,400	443,600	460,700
81.5	87.5	95.0	100.0	108.0	113.0	119.0	127.0	132.0	138.0	145.0	150.0
278,100	300,300	324,200	343,000	368,500	385,600	407,800	431,700	450,400	470,900	494,800	511,900
3.41	3.40	3.41	3.38	3.45	3.41	3.42	3.42	3.40	3.41	3.40	3.38
3.84	3.80	3.85	3.79	3.93	3.88	3.84	3.88	3.84	3.81	3.83	3.79
	1887 x 1880 x 890 (+60)						1887 x 2870 x 890 (+60)				
640	640	700	700	930	930	930	990	990	990	1050	1050
36.5/34.7/33.5	39.4/37.5/36.1	43.0/40.8/39.4	45.9/43.6/42.1	47.5/45.1/43.5	50.5/48.0/46.3	53.0/51.0/49.0	57.0/54.0/52.0	60.0/57.0/55.0	63.0/60.0/58.0	66.0/63.0/60.0	69.0/65.0/63.0
21.4	23.1	24.9	26.6	27.8	29.6	31.3	33.0	34.7	36.4	38.2	39.9
36.2/34.4/33.1	39.3/37.3/36.0	42.6/40.5/39.0	45.6/43.3/41.7	46.9/44.6/43.0	49.7/47.2/45.5	53.0/50.0/48.0	56.0/54.0/52.0	59.0/56.0/54.0	63.0/59.0/57.0	65.0/62.0/60.0	68.0/65.0/63.0
21.2	23.0	24.7	26.4	27.5	29.1	31.0	32.7	34.4	36.2	37.9	39.6
160+220	180+220	200+220	220+220	160+160+200	160+160+220	160+180+220	160+200+220	160+220+220	180+220+220	200+220+220	220+220+220
27.0	27.0	30.0	30.0	39.0	39.0	39.0	42.0	42.0	42.0	45.0	45.0
Ø 31.75	Ø 31.75	Ø 31.75	Ø 31.75	Ø 31.75	Ø 38.1	Ø 38.1	Ø 38.1	Ø 38.1	Ø 38.1	Ø 38.1	Ø 38.1
Ø 25.4	Ø 28.58	Ø 28.58	Ø 28.58	Ø 28.58	Ø 28.58	Ø 31.75	Ø 31.75	Ø 31.75	Ø 31.75	Ø 31.75	Ø 31.75
Ø 19.05	Ø 19.05	Ø 19.05	Ø 19.05	Ø 19.05	Ø 19.05	Ø 19.05	Ø 19.05	Ø 19.05	Ø 19.05	Ø 19.05	Ø 19.05
Ø 9.52	Ø 9.52	Ø 9.52	Ø 9.52	Ø 9.52	Ø 9.52	Ø 9.52	Ø 9.52	Ø 9.52	Ø 9.52	Ø 9.52	Ø 9.52
		Cooling: Dry: -10°C ~ +43°C D.B., Heating: -20°C ~ +15°C W.B. Simultaneous operation: -10°C ~ +43°C D.B.									
62	62.5	63.5	64	62.5	63	63	64.5	64.5	65	65.5	66
59	59.5	60.5	61	59.5	60	60	61.5	61.5	62	62.5	63
73	73.5	74.5	75	73.5	74	74	75.5	75.5	76	76.5	77