

| MODEL NO. | Indoor Unit | SAP-KR73EH | | SAP-KR93EH | | SAP-KR123EH | | SAP-KR73E | | SAP-KR93E | | SAP-KR123E | | |
|-----------------------------------|--|--------------------------|-----------------|---------------|----------|---------------|--|--------------------------|-----------------|---------------|----------|---------------|----|--|
| Outdoor Unit | Outdoor Unit | SAP-CR73EH | | SAP-CR93EH | | SAP-CR123EH | | SAP-CR73E | | SAP-CR93E | | SAP-CR123E | | |
| Performance | | | | | | | | | | | | | | |
| Capacity | kW | 2.45 | 2.75 | 2.78 | 3.32 | 3.55 | 4.20 | 2.41 | 2.65 | 3.72 | | | | |
| Air-circulation | (High) m ³ /h | 370 | 420 | 520 | 550 | 540 | 570 | 370 | 520 | 540 | | | | |
| Moisture removal | Liters/h | 1.30 | – | 1.60 | – | 2.00 | – | 1.30 | 1.60 | 2.00 | | | | |
| Electrical Rating | | | | | | | | | | | | | | |
| Phase, frequency | | 1 phase, 50Hz | | 1 phase, 50Hz | | 1 phase, 50Hz | | 1 phase, 50Hz | | 1 phase, 50Hz | | 1 phase, 50Hz | | |
| Voltage rating | V | 230 | | 230 | | 230 | | 230 | | 230 | | 230 | | |
| Available voltage range | V | 198-264 | | 198-264 | | 198-264 | | 198-264 | | 198-264 | | 198-264 | | |
| Running amperes | A | 3.73 | 3.68 | 4.20 | 4.20 | 5.40 | 5.30 | 3.50 | 4.10 | 5.30 | | | | |
| Power input | W | 815 | 805 | 920 | 920 | 1180 | 1165 | 750 | 880 | 1160 | | | | |
| Power factor | % | 95 | 95 | 95 | 95 | 95 | 96 | 93 | 93 | 95 | | | | |
| E.E.R./C.O.P | W/W | 3.01 | 3.42 | 3.02 | 3.61 | 3.01 | 3.61 | 3.21 | 3.01 | 3.21 | | | | |
| Features | | | | | | | | | | | | | | |
| Power sound level | <i>In.</i> Unit | dB-A | 44 | 44 | 45 | 45 | 47 | 47 | 44 | 45 | 47 | | | |
| Pressure sound level | <i>In.</i> Unit | dB-A | 36/34/32 | 35/33/32 | 38/36/32 | 37/35/42 | 41/36/32 | 40/36/42 | 36/34/32 | 38/36/32 | 40/36/32 | | | |
| (Measurement conform to JIS28731) | <i>at Quiet mode</i> | dB-A | – | – | – | – | – | – | – | – | | | | |
| Power sound level | <i>Out.</i> Unit | (High) dB-A | 57 | 57 | 58 | 58 | 58 | 58 | 57 | 58 | 58 | | | |
| Pressure sound level | <i>Out.</i> Unit | (High) dB-A | 46 | 47 | 47 | 48 | 49 | 50 | 46 | 47 | 49 | | | |
| Controls | Microprocessor | | | | | | Microprocessor | | | | | | | |
| Compressor type | Rotary (Hermetic) | | | | | | Rotary (Hermetic) | | | | | | | |
| Fan speed | 3 Speed + Auto/1 (Hi) | | | | | | 3 Speed + Auto/1 (Hi) | | | | | | | |
| Timer | ON/OFF 24 hour & Daily program, 1-hour Off | | | | | | ON/OFF 24 hour & Daily program, 1-hour Off | | | | | | | |
| Air-deflection | Horizontal | Manual | | | | | | Manual | | | | | | |
| | Vertical | Auto | | | | | | Auto | | | | | | |
| Air filter | Washable & AntiMold | | | | | | Washable & AntiMold | | | | | | | |
| Air clean filter | Dust-collecting & Deodorizing | | | | | | Dust-collecting & Deodorizing | | | | | | | |
| Panel | Removable & Washable | | | | | | Removable & Washable | | | | | | | |
| Remote controller | With Holder/Address SW | | | | | | With Holder/Address SW | | | | | | | |
| Max.allowable at shipment | m | 7.5 | | | | | | 7.5 | | | | | | |
| Ref.dia.Na/Wi.Pipe | mm(in) | 6.35 (1/4) / 9.525 (3/8) | | | | | | 6.35 (1/4) / 9.525 (3/8) | | | | | | |
| Refrigerant type | R410A | | | | | | R410A | | | | | | | |
| Dimensions & Weight | | | | | | | | | | | | | | |
| Indoor Unit | H/W/D | mm | 285 x 825 x 189 | | | | | | 285 x 825 x 189 | | | | | |
| Outdoor Unit | H/W/D | mm | 548 x 720 x 265 | | | | | | 548 x 720 x 265 | | | | | |
| Net weight | Indoor Unit | kg | 8.50 | | | | 9 | | 8.25 | | | | 9 | |
| Net weight | Outdoor Unit | kg | 31 | | 28 | | 35 | | 27 | | 28 | | 34 | |

Specifications subject to change without notice

Measurements conform to JIS 9612 standards

| | Cooling | Heating |
|-------------------------|---------------------|-------------------|
| Indoor air temperature | 27°C D.B./19°C W.B. | 20°C D.B./– |
| Outdoor air temperature | 35°C D.B./24°C W.B. | 7°C D.B./6°C W.B. |

Operating range

| | Temperature | Indoor Air Intake Tmp. | Outdoor Air Intake Tmp. |
|---------|-------------|------------------------|-------------------------|
| Cooling | Maximum | 32°C D.B./23°C W.B. | 43°C D.B./– |
| | Minimum | 19°C D.B./14°C W.B. | 19°C D.B./– |
| Heating | Maximum | 27°C D.B./– | 24°C D.B./18°C W.B. |
| | Minimum | 16°C D.B./– | –8°C D.B./–9°C W.B. |