

| MODEL NO. | Indoor Unit | SPW-KR254GH56 SPW-CR254GVH56 | | SPW-KR254GH56 SPW-CR254GV56 |
|---------------------------------------|--------------------------|---------------------------------|-------------|--------------------------------|
| Outdoor Unit | Outdoor Unit | Cooling | Heating | Cooling |
| Performance | | | | |
| Capacity | kW | 2.2/7.1/8.0 | 2.2/8.0/9.0 | 2.2/7.1/8.0 |
| Air-circulation | (High) m ³ /h | 1140 | | 1140 |
| Moisture removal | Liters/h | 4.0 | | 4.0 |
| Electrical Rating | | | | |
| Phase, frequency | | 1 phase, 50Hz | | 1 phase, 50Hz |
| Voltage rating (AVR) | V | 230 | | 230 |
| Running amperes | A | 12.70 | 12.20 | 12.70 |
| Power input | W | 2.36 | 2.26 | 2.36 |
| E.E.R./C.O.P | W/W | 3.01 | 3.54 | 3.01 |
| Features | | | | |
| Power sound level In. Unit | (H/M/L) dB-A | 52/48/45 | | 52/48/45 |
| Pressure sound level In. Unit | (H/M/L) dB-A | 41/37/34 | | 41/37/34 |
| Power sound level Out. Unit | (H) dB-A | 58 | 60 | 58 |
| Pressure sound level Out. Unit | (H) dB-A | 47 | 49 | 47 |
| | at Quiet mode dB-A | 45 | | 45 |
| Ref.dia.Na/Wi.Pipe | mm(in) | 9.52 (3/8) / 15.88 (5/8) | | 9.52 (3/8) / 15.88 (5/8) |
| Refrigerant type | | R410A | | R410A |
| Dimensions & Weight | | | | |
| Indoor Unit | H/W/D | 330 x 1140 x 228 | | 330 x 1140 x 228 |
| Outdoor Unit | H/W/D | 780 x 940 x 340 | | 780 x 940 x 340 |
| Net weight | Indoor Unit | 21 | | 21 |
| Net weight | Outdoor Unit | 58 | | 58 |

Specifications subject to change without notice

Measurements conform to JIS 9612 standards

Operating range

| | Cooling | Heating |
|-------------------------|---------------------|-------------------|
| Indoor air temperature | 27°C D.B./19°C W.B. | 20°C D.B./– |
| Outdoor air temperature | 35°C D.B./– | 7°C D.B./6°C W.B. |

- Cooling operation -15°C to 43°C
- Heating operation -15°C to 15°C