

MODEL NO.		SPW-CR363GVH8		SPW-CR483GVH8		SPW-CR703GVH8		SPW-CR903GVH8		
Outdoor Unit	Outdoor Unit	SPW-CR363GV8		SPW-CR483GV8		SPW-CR703GV8		SPW-CR903GV8		
Performance		Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating	
Capacity	kW	11.20	12.5	14.0	16.0	22.40	25.0	28.0	31.5	
	BTU/h	38,200	42,700	47,800	54,600	76,400	85,300	95,500	107,500	
Air-circulation	(High) m ³ /min(ft ³ /min)	84 (2790)		84 (2790)		155 (5470)		150 (5300)		
Electrical Rating										
Phase, frequency		3 phase, 50Hz		3 phase, 50Hz		3 phase, 50Hz		3 phase, 50Hz		
Voltage rating		380-400-415		380-400-415		380-400-415		380-400-415		
Running amperes		A	7.9/7.9/7.9	8.0/7.7/8.0	9.5/9.5/9.4	9.0/8.9/8.9	15.8/15.2/14.9	14.2/13.7/13.5	18.8/18.3/18.0	17.5/17.0/16.9
Power input		W	4.62/4.60/4.64	4.69/4.52/4.68	5.54/5.61/5.65	5.30/5.27/5.32	9.45/9.50/9.56	8.52/8.57/8.62	11.3/11.4/11.5	10.4/10.6/10.8
E.E.R./C.O.P		W/W	2.42/2.43/2.41	2.67/2.77/2.67	2.53/2.50/2.48	3.02/3.04/3.01	2.37/2.36/2.34	2.93/2.92/2.90	2.48/2.46/2.43	3.03/2.97/2.92
Compressor locked rotor amperes		A	51/53/55		62/65/67		51/53/55		62/65/67	
Features										
Power sound level		(H) dB-A	66		66		69		69	
Pressure sound level		(H) dB-A	55		55		58		58	
Ref.dia.Na/Wi.Pipe		mm(in)	9.52 (3/8) / 19.05 (3/4)		9.52 (3/8) / 19.05 (3/4)		12.7 (1/2) / 25.4 (1)		12.7 (1/2) / 28.58 (1-1/8)	
Refrigerant type			R407C		R407C		R407C		R407C	
Dimensions & Weight										
H/W/D		mm	1235 x 940 x 340		1235 x 940 x 340		1218 x 883 x 883		1218 x 883 x 883	
Net weight		kg	120		120		GVH8: 231 / GV8: 229		GVH8: 243 / GV8: 241	

Specifications subject to change without notice