

HP			4	5	6	
Model name			SPW-CR365GXH56	SPW-CR485GXH56	SPW-CR605GXH56	
Power supply			220-240V - 13 phase, 50, 60Hz			
Capacity	Cooling	kW	11.2	14.0	15.5	
		BTU/h	38,200	47,800	52,900	
	Heating	kW	12.5	16.0	17.6	
		BTU/h	42,700	54,600	60,000	
C.O.P.	Cooling	kW	4.06	3.66	3.39	
	Heating	kW	4.34	4.10	3.84	
Dimensions (HxWxD)		mm	1230 x 940 x 340			
Net weight		kg	130			
Electrical ratings	Cooling	Running amperes	A	14.1	19.6	23.4
		Power input	kW	2.76	3.83	4.57
	Heating	Running amperes	A	14.7	19.9	23.4
		Power input	kW	2.88	3.90	4.58
Air-circulation		(m ³ /min)	95			
Refrigerant amount at shipment		kg	4.0			
Piping connections	Gas pipe	mm	Ø 19.88		Ø 19.05 (Socket is attached)	
	Liquid pipe	mm	Ø 9.52			
Ambient temperature operating range			Cooling: -10°C ~+43°C D.B., Heating: -20° C ~+15°C W.B.			
Pressure sound	Normal mode	dB-A	51/52	52/53	53/54	
	Silent mode	dB-A	48/49	49/50	50/51	
Power sound	Normal mode	dB-A	62/63	63/64	64/65	

Specifications subject to change without notice