

MODEL NO.	Indoor Unit	SPW-UR183GHN56 SPW-CR183GHL5		SPW-UR253GHN56		SPW-CR253EHL8		SPW-UR363GHN56 SPW-CR363EHL8		SPW-UR483GHN56 SPW-CR483GHL8	
Outdoor Unit	Outdoor Unit	Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating
Performance											
Capacity	kW	5.60	6.30	7.30	8.60	7.30	8.60	10.60	12.50	12.60	15.30
Air-circulation	(High) m ³ /h	720		1080		1080		1800		1980	
Moisture removal	Liters/h	3.00		3.50		3.50		4.20		5.40	
External static pressure	(High) Pa	40		50		50		78		78	
External static pressure with booster cable	Pa	62		92		92		122		113	
Electrical Rating											
Phase, frequency		1 phase, 50Hz		1 phase, 50Hz		3 phase, 50Hz		3 phase, 50Hz		3 phase, 50Hz	
Voltage rating (AVR)	V	230		230		400		400		400	
Running amperes	A	11.3	11.6	13.5	14.8	4.67	5.20	7.16	7.80	8.49	9.65
Power input	W	2460	2550	2940	3190	2990	3020	4090	4470	4760	5750
E.E.R./C.O.P	W/W	2.27	2.47	2.48	2.70	2.70	2.85	2.59	2.80	2.65	2.75
Features											
Power sound level In. Unit	(H/M/L) dB-A	47/44/41		45/41/39				49/44/42		51/48/44	
Pressure sound level In. Unit	(H/M/L) dB-A	36/33/30		34/30/27				38/33/31		40/37/33	
Power sound level Out. Unit	(H) dB-A	63		63				64		66	
Pressure sound level Out. Unit	(H) dB-A	52		52				53		55	
Ref.dia.Na/Wi.Pipe	mm(in)	6.35 (1/4) / 15.88 (5/8)		6.35 (1/4) / 15.88 (5/8)		6.35 (1/4) / 15.88 (5/8)		9.52 (3/8) / 19.05 (3/4)		9.52 (3/8) / 19.05 (3/4)	
Refrigerant type		R407C		R407C		R407C		R407C		R407C	
Dimensions & Weight											
Indoor Unit	H/W/D mm	310 x 700 x 630		310 x 1000 x 630				310 x 1480 x 630		310 x 1480 x 630	
Outdoor Unit	H/W/D mm	735 x 940 x 340		735 x 940 x 340				1235 x 940 x 340		1235 x 940 x 340	
Net weight	Indoor Unit kg	25		32				47		47	
Net weight	Outdoor Unit kg	68		71				106		108	

Specifications subject to change without notice

Measurements conform to JIS 9612 standards

	Cooling	Heating
Indoor air temperature	27°C D.B./19°C W.B.	20°C D.B./-
Outdoor air temperature	35°C D.B./24°C W.B.	7°C D.B./6°C W.B.

Operating range

	Temperature	Indoor Air Intake Tmp.	Outdoor Air Intake Tmp.
Cooling	Maximum	32°C D.B./23°C W.B.	43°C D.B./-
	Minimum	19°C D.B./14°C W.B.	19°C D.B./-
Heating	Maximum	27°C D.B./-	24°C D.B./18°C W.B.
	Minimum	16°C D.B./-	-8°C D.B./-9°C W.B.